

FIXED INDOOR COLOUR CAMERA WITH VARIFOCAL LENS.

FEATURES AND BENIFITS

- Medium (LTC0485) and high (LTC 0610) sensitive colour camera. Dome camera (LTC1421/10)
- Only one coaxial cable and power cable required for proper operation.
- Provided with a wide range vary-focal auto iris lens 5-50mm including a wall or ceiling bracket for easy field installation.
- Different power supplies and video standards available. (USA or Europe)



(Shown with vary-focal auto iris lens 4-10mm and wall/ceiling bracket. Model LTC 0485 will have approx. same lay-out)



Model LTC 1423/10

Mini dome fixed colour camera 6mm lens
LTC 1421/10 and LTC 1422/10 will have same lay-out

The model LTC0485 (medium sensitive), LTC0610 (high sensitive) and LTC 1421/10 up to LTC 1423/10 are colour camera units provided with a fixed lens of 2mm, 3 mm or 6mm (Dome) or variable lens between 5-50mm or 4-10mm (LTC 0485 and LTC 0610). Lens to be adjusted once by hand upon site requirements.

Only a coaxial cable (or fiber) and power supply cabling is required for proper operation.

The model LTC0485 is ideal for general-purpose applications into any indoor area and the model LTC0610 is highly recommended for applications under low light level or heavy backlight applications.

The LTC 1421/10 up to LTC1423/10 dome cameras are ideal for mounting against a false ceiling on which limited space is available.

Specifications	LTC0485	LTC0610	LTC 1421/10 up to LTC1423/10.
Power consumption	: 4Watt/230VAC or 12 to 24VAC	4Watt/230VAC or 12 to 24VAC	2Watt/12-28VAC or DC
Minimum scene illumination	: 0,4 Lux day mode, 0,15 lux night mode at F=1,2	0,23 Lux day mode, 0,095 Lux night mode	4,5 Lux (Full video at 22Lux)
CCD image sensor	: 1/3 " 752Hx582V .	1/2 " 752Hx582V	1/4 "
Resolution	: 540TV lines	540TV lines	470TV lines
Back light compensation (BLC)	: Yes	Yes	Yes
Dimensions (LxHxW)mm	: 133x59x67mm	133x59x67mm	Ø115x77mm
Lens	: variable focus 5-50mm F=1,8	variable focus 4-10mm F=1,8	Fixed focal length of 2mm, 3mm or 6mm
Protection camera	: IP23	IP23	IP23
Temperature range camera:	: Minus 20C° to +50C°	Minus 20C° to +50C°	Minus 10C° to +45C°
Shipping weight	: 0,82 Kg (Incl.lens)	0,82 Kg (incl.lens)	0,4 Kg

PRONOR N.V.
Liefkensstraat 35A
B-9032 GENT

TEL: (+) 32-9-257 08 80
FAX: (+) 32-9-257 08 85

www.pronorbelgium.com
E-mail: info@pronor.be