

## DIGITAL MASTER STATION MODEL EE380/K-12 up to K48.



### Model EE380-K48

Digital master station with 48 illuminated selection buttons  
(Model EE380-K12, K24 and K36 will have same lay-out)

#### Specifications.

Construction	: black moulded shockproof ABS.
Mounting	: desk top, inclination bracket included.
Power requirements	: 12-24VAC/10VA or 15-35VDC/10W.
Cabling	: Standard telephone cable 1x2x0,6mm <sup>2</sup> (2Km) and separate power supply.
Microphone	: Electret. External connection for headphone-headset or handset.
Audio amplifier	: 1,5Watt with special built in speaker membrane.
Adjustments	: volume and ringing tone. Use the up/down arrow.
Frequency range	: 200Hz - 9500Hz
Display	: Illuminated full graphic, 8 lines to 14 characters each.
Keyboard	: Up to 48 illuminated LED membrane selection switches. 3 colour LED function.
Technology	: latest DSP speech technology for clear communication.
Protection	: IP50
Temperature range	: 0C° to +60C°. (95% humidity)
Dimensions (WxHxD)	: 245x68x324mm (Gooseneck not included)
Shipping weight	: 1,1Kg



### 3 colour LED function



### Model EE380

(No extension keypads "-Kxx" included)

The models EE380/K-12 up to K48 are professional master intercom stations modular constructed for up to 48 freely programmable LED illuminated selection buttons. Available as desk version or flush mount version the EE380 units are ideal for integration in system consoles in control rooms or as Zone call microphones in a Public Address system.

The communication is semi-duplex (speak/listen function controlled by voice). All stations are provided with a red optical indication soon the microphone of the station is activated.