

INDUSTRIAL INDOOR/OUTDOOR INTERCOM PAGE/PARTY STATIONS

Model 700-102 Indoor single party station
Consist of: - 701-302 handset amplifier



Model 7005-102 Indoor Multiparty station
Consist of: - 701-302 handset amplifier



Model 730-104 Outdoor station single party
Consist of: - 701-302 handset amplifier.
- 733-001 Outdoor enclosure

Model 7305-104 Outdoor station Multi-party. (Not shown)
Consist of: - 701-302 handset amplifier

- 7335-001 Outdoor enclosure

FEATURES AND BENEFITS

- Noise-cancelling microphone allows communication in high noise areas.
- Non movable electronic hookswitch for added durability.
- Hazardous area approvals.
- Ample space in enclosure and double row terminal block for easy installation.
- Maximum distance 1.6Km between two stations. (Up to 5Km with optionally fibre converter)
- Modular design reduces spare part investment.
- Rugged steel dust-tight housing (indoor) corrosive agents.
- Hearing Aid Compatible



Model 10401-201

Headset allows handsfree communication.

Model 700/7005 indoor Wall stations and model 730/7305 Outdoor Wall stations provide quality all-page and common-talking communications.

Available in single-or multi-party line models, each unit includes a handset amplifier and a 12-Watt speaker amplifier. The Model 700 and 7005 indoor wall stations are housed in dust-tight, 2-mm cold-rolled steel enclosures finished with textured polyurethane paint. The handsets are standard provided with a 1,8 meter long coil cord and can be provide as option with 4 meter (add HY15) or 7meter (add HY25) long coil cord. See datasheet Pub-0003-011, 12 and 21 for speakers and Pub-0003-056, 103 and 104 for proper installation cables and installation accessories.

Specifications.

Installation : Use special cable 60023-201/SPL. See datasheet Pub-0003-056.

Power : 120VAC 50/60Hz 50VA consumed (4VA idle) or 230VAC using transformer. See datasheet Pub-0003-103

Audio amplifier : 12Watt RMS. Frequency range 250-4KHz

Microphone : Dynamic 10 Ohm noise cancelling.

Controls : Speaker volume, receiver volume, mic volume, anti-side tone.

Temperature range : Minus 30C° to +70C°

Dimensions : Indoor stations - Model 700-102: (WxHxD)=205x205x220mm

- Model 7005-102: 205x307x220mm

: Outdoor stations - Model 730-104: (WxHxD)=213x370x280mm

- Model 7305-104: 213x370x280mm

Shipping weight : Amplifier :3,1 Kg Enclosure: 3,4Kg (Indoor) : 4,4Kg (Outdoor)

Protection : Indoor IP42 Outdoor IP 65

PRONOR N.V.

Liefkensstraat 35A

B-9032 GENT

TEL: (+) 32-9-257 08 80

FAX: (+) 32-9-257 08 85

www.pronorbelgium.com

E-mail:info@pronor.be