

## “EZ PAGE” OUTDOOR TALK BACK INTERCOM.



**Model GC-AC2**

(Models GC-AC1 and DC1 will have the same outline)

### FEATURES AND BENIFITS

- Master/slave configuration (switchable) and handsfree operation. Accepts footswitch.
- Rugged construction.
- Easy to use and to install. No software required.
- 8Watt RSM amplifier.
- Suitable up to maximum 75dB(A) ambient noise.
- Daisy chain wiring by using cable 60023-201/SPL.
- Suitable for wall mounting.

The “EZ Page” intercom provides simplex communication (push to talk, release to listen) for simply reliable, easy to use communication for industrial applications such as production lines, automotive plants and light industry.

The “EZ Page” is available in two standard configurations: Master/slave and common line.

In the Master/slave system, the master controls the listen/talk function. In the Common line system the user can call everywhere simultaneous.

### Specifications

Power requirements	: 230VAC–120VAC–24DC all 28VA.and 50/60Hz. Specify tension when ordering.
Wiring	: By system cable 60023-203/SPL (8core) covering power and communication. Use junction box JB-0023/EZ for easy installation.
Temperature range	: Minus 40C to +70C
Protection	: IP56
Construction	: Cast aluminium RAL 5017 (Blue). Station provided with two (2) times' 3 meter cable for connection to the system cable.
Cable entry	: Two (2) PG 13,5
Sound power	: 8Watt/RMS producing 113dB at one 1meter full power.
External controls	: Volume control and push to talk switch.
Dimensions (LxWxD)	: 285x177x138
Shipping weight	: 5Kg