

ANALOGUE PROFESSIONAL INTERCOM STATIONS



Model EE400G

| | |
|------------------------|---|
| <u>Specifications.</u> | |
| Construction | : Grey or black moulded shock proof ABS provided with 3mtr connection cable with RJ 11 connector. |
| Mounting | : Desk top or wall mounted with bracket EW401G. |
| Power requirements | : Drawn from the central exchange. |
| Cabling | : Standard telephone cable 2x2x0,6mm2 (2Km) |
| Microphone | : Electret |
| SPL (1Watt/1Mtr) | : 82dB at 50-Ohm speaker. |
| Frequency range | : 200Hz - 12KHz |
| Protection | : IP50 |
| Keyboard | : Encapsulated REED contacts. |
| Temperature range | : Minus 40C to +90C. (95% humidity) |
| Dimensions (LxWxD) | : 230x66x54mm |
| Shipping weight | : 0,4Kg |



Model EE401G

| | |
|--------------------|---|
| Construction | : Grey or black moulded shock proof ABS provided with 3mtr connection cable with RJ 11 connector. |
| Mounting | : Desk top or wall mounted with bracket EW401G. |
| Power requirements | : Drawn from the central exchange. |
| Cabling | : Standard telephone cable 2x2x0,6mm2 (1,8Km) |
| Microphone | : Electret |
| SPL (1Watt/1Mtr) | : 82dB at 50-Ohm speaker. |
| Frequency range | : 200Hz - 12KHz |
| Protection | : IP50 |
| Keyboard | : Encapsulated REED contacts. |
| Display | : 6x16 segments LCD |
| Temperature range | : Minus 40C to +90C. (95% humidity) |
| Dimensions (LxWxD) | : 230x66x54mm |
| Shipping weight | : 0,4Kg |



Model EE472B

(Model EE470 will have no display)

| | |
|--------------------|---|
| Construction | : Grey (G) or black (B) moulded shock proof ABS including 3mtr connection cable with RJ 11 connector. |
| Mounting | : Desk top. |
| Power requirements | : Drawn from the central exchange. |
| Cabling | : Standard telephone cable 2x2x0,6mm2 (1,8Km) |
| Microphone | : Noise compensating gooseneck microphone. |
| SPL (1Watt/1Mtr) | : 82dB at 50-Ohm speaker. |
| Frequency range | : 200Hz - 9000Hz |
| Protection | : IP50 |
| Keyboard | : Encapsulated REED contacts. |
| Display | : 6x16 segments LCD |
| Temperature range | : Minus 40C to +90C. (95% humidity) |
| Dimensions (LxWxD) | : 230x66x54mm |
| Shipping weight | : 0,4K |



Model EE472G/FL

(Model EE470G/FL will have no display)

| | |
|--------------------|--|
| Construction | : Grey or black moulded shock proof ABS with aluminium mounting plate. |
| Mounting | : Flush mounted. |
| Power requirements | : Drawn from the central exchange. |
| Cabling | : Standard telephone cable 2x2x0,6mm2 (1,8Km) |
| Microphone | : Noise compensating gooseneck microphone. |
| SPL (1Watt/1Mtr) | : 82dB at 50-Ohm speaker. |
| Frequency range | : 200Hz - 9000Hz |
| Keyboard | : Encapsulated REED contacts. |
| Display | : 6x16 segments LCD |
| Temperature range | : Minus 40C to +90C. (95% humidity) |
| Dimensions (HxWxD) | : 260x132x50mm |
| Shipping weight | : 1Kg |

Above models are indoor intercom masterstations for office, stock rooms, and administration applications.

The communication is semi-duplex (speak/listen function controlled by voice). All stations are provided with a red optical indication soon the microphone of the station is activated.