

TELEPHONE SIGNAL COMBINED UNITS.



Model FSK
(Amber colour shown)

Specifications.

Construction	: Black seawater-proof cast aluminium with black plastic coating. Flash light cap in Polycarbonate and can be ordered in following colours: Transparent Red Amber Green Blue
Mounting	: Unit is provided with two (2) glands M20 . : Wall mounting with two screws.
Power requirements	: 230VAC at 130mA and separately power drawn from telephone line. Designed for continuously operation.
Flash frequency	: In sequence with telephone calling signal.
Sound volume	: 105 dB(a) at one (1) meter. Four (4) different tones selectable by DIP switch.
Protection	: IP66
Temperature range	: Minus 20C° to +70C° . (95% humidity)
Dimensions (WxHxD)	: 150x195x104mm
Shipping weight	: 1,5Kg



Model eFSK
(Amber colour shown)

Specifications.

Construction	: Black seawater-proof cast aluminium with black plastic coating. Flash light cap in Polycarbonate and can be ordered in following colours: Transparent Red Amber Green Blue
Mounting	: Unit is provided with two (2) glands M20 : Wall mounting with two screws.
Power requirements	: 230VAC and separately power drawn from telephone line. Designed for continuously operation.
Flash frequency	: In sequence with telephone calling signal.
Sound volume	: 90 dB(a) at one (1) meter. Eight (8) different Tones seleatable by DIP switch.
Protection	: IP66
Approval	: ATEX approval EEX(ib) em IIC T6
Temperature range	: Minus 20C° to +40C° . (95% humidity)
Dimensions (WxHxD)	: 150x195x104mm
Shipping weight	: 1,5Kg

The model FSK is a combined acoustic and optical telephone bell indicator. The unit is ideal as extra bell in areas where noise level is too high for a standard telephone bell.

The model eFSK is the explosion proof version suitable for use in a zone 1 and 2 area. Both units require 230VAC as well connection with the telephone line for correct operation.