

## INDUSTRIAL TELEPHONES



**Model 256-001 Weatherproof telephone**


### FEATURES AND BENIFITS

- Extreme operating temperature. Suitable for wall mounting.
- Anti-Corrosive enclosure.
- Robust and IP65 weather resistant.
- Noise cancelling microphone included.
- Electronic ringer. No moving parts.

### **Model 246-001 Indoor telephone**

#### **Options**

- SK = Spring kit for door. (Model 256-001 only)  
 AR = armoured coil cord.  
 REC = Recall button in order to transfer a conversation.  
 FSK = External flash/sounder. See datasheet Pub-0003-029 for details.



Models 246-001 and 256-001 are industrial indoor (246-001) or outdoor (256-001) telephones built to withstand operator abuse and environmental extremes. The telephone has no moving parts which provides the user with a high level of reliability. Both types will have standard receiver volume knob built into the handset and are provided with a noise-cancelling microphone.

This telephone exists as well without keypad in order to operate as emergency or hotline telephone. Just lifting the handset will automatically ring a pre-programmed phone number.

#### **Specifications.**

Power requirements	: 24VDC...60VDC non polarity sensitive and drawn from the telephone line.
Ringing tone	: 92dB(a) at one (1) meter. (84dB(a) with door closed)
Ringer equivalent	: REN 1.3B
Hook switch	: Reed contact.
Dialling system	: DTMF
Temperature range	: Minus 40C° to +60C°
Protection	: IP32 (model 246-001) IP65 (model 256-001)
Dimensions (HxWxD)	: Model 246-001 : 242x204x174mm : Model 256-001 : 330x235x190mm
Shipping weight	: Model 246-001 : 2,5Kg    Model 256-001 : 5,2Kg

**PRONOR N.V.**  
 Liefkensstraat 35A  
 B-9032 GENT

TEL: (+) 32-9-257 08 80  
 FAX: (+) 32-9-257 08 85

www.pronorbelgium.com  
 E-mail: info@pronor.be