

LCD (TFT) FLAT COLOR MONITOR 17" and 19"




Model SMT-1922 (19")
(Model SMT-1722 (17") will have same lay-out)

FEATURES AND BENIFITS


- Composite video BNC input with through loop, VGA and S-video.
- High resolution , more than 600TV lines PAL and NTSC.
- Fast response 5ms and tempered glass screen.
- 100V...240VAC power supply .

Wall & Ceiling brackets

Monitor comes with desk bracket. Below noted wall brackets are not included with the monitors and must be ordered separately.



VFW226
(Wall)



VFW 426
(Wall)

The models SMT-1722 and SMT-1922 are LCD (TFT) flat screens for direct use on a CCTV system.

Those flat screens provide an excellent picture and needs very little space. This allows use on places where free space is an important matter such like on desks in control rooms. Those flat screens are totally free of "flashing" and radiation. The main controls can be done by using the push buttons situated on the monitor.

Specifications.

	<u>SMT-1722</u>	<u>SMT-1922</u>
Construction	PVC housing black	PVC housing black
Power requirements	100 - 240VAC/50-60Hz via external adapter	100 - 240VAC/50-60Hz via external adapter
Power consumption	42Watt	42Watt
Input signal	BNC with trough loop1V PTP composite video, VGA 15-pins and S-Video	BNC with trough loop1V PTP composite video, VGA 15-pins and S-Video
Usable view angle Horiz.	160°	160°
Size screen	17"	19"
Horizontal resolution	More than 600TV lines	More than 600TV lines
Brightness (cd/m ²)	300	300
Contrast ration	1000:1	1000:1
Response time	5ms	5ms
Protection	IP23	IP23
Dimensions WxHxD	371x332(368)x50(220)mm	412x359(398)x50(220)mm
() = with desk bracket		
Shipping weight	6Kg	7Kg
Mounting bracket	...VESA standard. Desk bracket for free standing including. Other brackets available as option	
Temperature range	+0C° to +40C°	