

## DIGITAL MICROPHONE STATION WITH or WITHOUT ALARM BUTTONS



**Connection box**

**Model APS-308**

### Specifications.

Construction	: Black metal housing provided with 2,5mtr cable to connection box.
Mounting	: Desk top, wall or flush mounted.
Power requirements:	Drawn from central cabinet.
Cabling	: Twisted and screened per pair 2x2x0,6mm <sup>2</sup> (700mtr)
Microphone	: Gooseneck electret.
Push buttons	: maximum 8 selection buttons
Frequency range	: 200Hz - 9000Hz
Protection	: IP50
Zone sel. buttons	: Incorporated : membrane type.
Temperature range	: 0C° to +50C°. (95% humidity)
Dimensions (LxWxD):	180x80x45mm.
Shipping weight	: 1,3Kg.



**Connection box**



**Model APS-308/AL-3**

(Connection box not shown. Model APS-308/AL-1 and AL-2 will have same look and having 1 or 2 alarm buttons.)

### Specifications.

Construction	: Black metal housing provided with 2,5mtr cable to connection box.
Mounting	: Desk top, wall or flush mounted.
Power requirements:	Drawn from central cabinet.
Cabling	: Twisted and screened per pair 2x2x0,6mm <sup>2</sup> (700mtr)
Microphone	: Gooseneck electret.
Zone sel. buttons	: Maximum 8 selection buttons.
Alarm buttons	: maximum 3 buttons.
Frequency range	: 200Hz - 9000Hz
Protection	: IP50
Push buttons	: Incorporated : membrane type.
	Mounted on surface: Protected with transparent protection covers.
Temperature range	: 0C° to +50C°. (95% humidity)
Dimensions (LxWxD):	180x160x45mm.
Shipping weight	: 2,1 Kg.

Model APS-308 is a digital microphone station for Public Address applications.

The microphone station can have minimum 1 and as maximum 8 zone selection buttons. Those buttons can be programmed by using a standard PC to have a customised function.

The microphone station can be provided with surface mounted alarm buttons in order to start several alarm tones. The alarm push buttons are provided with a transparent protective cover to avoid accidental touching.

### **PRONOR N.V.**

Liefkensstraat 35A  
B-9032 GENT

Pub-0003-071a

TEL: (+) 32-9-257 08 80

FAX: (+) 32-9-257 08 85

www.pronorbelgium.com

E-mail:pronor@skynet.be

## DIGITAL MICROPHONE STATION WITH ALARM BUTTONS



### **Model APS-316**

(Connection box not shown. Model APS-308...364 will have same look and having 8 or 24 push buttons.)

### Specifications.

Construction	: Black metal housing provided with 2,5mtr cable to connection box.
Mounting	: Desk top, wall or flush mounted.
Power requirements	: Drawn from central cabinet.
Cabling	: Twisted and screened per pair 2x2x0,6mm <sup>2</sup> (700mtr)
Microphone	: Gooseneck electret.
Push buttons	: maximum 364selection buttons
Alarm buttons	: as per customer specification. (5 each show)
Frequency range	: 200Hz - 9000Hz
Protection	: IP50
Push buttons	: Incorporated : membrane type. Mounted on surface: Protected with transparent protection covers.
Temperature range	: 0C° to +50C°. (95% humidity)
Dimensions (LxWxD)	: variable upon type.
Shipping weight	: variable upon type.

---

Model APS-308 (up to 364) is a digital microphone station for Public Address applications.

The microphone station can have minimum 1 and as maximum 64 zone selection buttons. Those buttons can be programmed by using a standard PC to have a customised function.

The microphone station can be provided with surface mounted alarm buttons in order to start several alarm tones. The alarm push buttons are provided with a transparent protective cover to avoid accidental touching.

---

### **PRONOR N.V.**

Liefkensstraat 35A  
**B-9032 GENT**

Pub-0003-071

TEL: (+) 32-9-257 08 80  
FAX: (+) 32-9-257 08 85

www.pronorbelgium.com  
E-mail:pronor@skynet.be