

CLEAN ROOM TELEPHONE



Model 295F

FEATURES AND BENIFITS

- DTMF dialling. Suitable for flush mounting.
- Two (2) autodial buttons.
- Oversized buttons allows easy operation for gloved hands.
- Completely smooth front panel is sealed with an overlay that keeps the phone particulate-free.
- Remote programming.



Model 237-003

The model 295F is a hand-free telephone for use in clean room. The visual graphics are printed on the reverse side of the overlay to prevent particulate shedding and to ensure longevity. The telephone requires an analogue (a,b) telephone line.

Operation is simple: two autodial buttons connect the caller with pre-programmed numbers and the fully functional keypad allows standard telephone operation.

Each model 295 requires connection to a power supply model 237-003. This power supply can accept maximum three (3) clean phones model 295F and must be ordered separately.

<u>Specifications.</u>	<u>295F</u>	<u>237-003</u>
Power requirements	: 48VDC stabilised at 0,25A provided by model 237-003	100-240VAC 50/60Hz Max. 3 clean phone model 295
Ringing tone	: 85dbA at one (1) meter at full power.	
Ambient noise limit	: Do not use above the 75 dB(A) ambient noise.	
Programming	: Remote DTMF.	
Ringer equivalent	: REN 0,4B	
Dialling system	: DTMF	
Temperature range	: Minus 20C to +60C	Minus 20C to +60C
Protection	: IP66	IP66
Dimensions (LxWxD)	: 305x305x44mm	220x165x100mm
Shipping weight	: 4,8Kg	1,9Kg