

MOVABLE INDUSTRIAL OUTDOOR COLOUR CAMERA IP66



Model PR-MCC-002

(Shown with optionally wash & whipe.
Model PR-MCC-001 will have same layout)

FEATURES AND BENIFITS

- Medium (PR-MCC-001) and high (PR-MCC-002) sensitive colour camera.
- Only one coaxial cable and power cable required. No extra camera control cable required.
- Provided with weatherproof Amphenol connectors for easy field installation.
- Different power supplies and video standards available. (USA or Europe)
- Built in telemetry unit for remote control.
- Automatic Day/Night sense increasing visibility during night.

Options.



Wash & whipe (WW)



Bird anti-landing (BAL)

The model PR-MCC-001 (medium sensitivity) and PR-MCC-002 (high sensitivity) are colour camera units provided with a 10 times remote controlled zoom lens, a moving mechanism (P&T) and a built in telemetry receiver avoiding any extra cabling between the camera and the control unit. Only a coaxial cable and power supply is required.

The model PR-MCC-001 is ideal for general-purpose applications into an industrial area and the model PR-MCC-002 is highly recommended for process survey or site access video control requiring high definition picture at low illumination.

Both types can be provided with several options such as wash & whipe device (WW), explosion proof housing and motor (EXM), fiber optic transmitters for video and data transport (FIB).

Specifications.

Power consumption

Minimum scene illumination

CCD image sensor

Resolution

Dimensions (LxHxW)mm

Lens

P&T motor speed

Protection camera

Temperature range camera:

Shipping weight

PR-MCC-001

: 25Watt/120-230VAC or 24VDC-AC

Specify power when ordering.

: 0,12Lux night mode, 0,3 Lux day mode at F=1,2

: 1/3 " 752Hx492V .

: 540TV lines

: 660x420x240mm

: Motorised zoom 6-60mm F=1,2

: 6°/sec pan 3°/sec tilt

: IP66

: Minus 20C° to +50C°

: 14 Kg

PR-MCC-002

: 25Watt/120-230VAC or 24VDC-AC

Specify power when ordering.

: 0,08 Lux night mode, 0,18 Lux day mode

: 1/2 " 752Hx582V

: 540TV lines

: 660x420x240mm

: Motorised zoom 8-80mm F=1,2

: 6°/sec pan 3°/sec tilt

: IP66

: Minus 20C° to +50C°

: 14 Kg

PRONOR N.V.

Liefkensstraat 35A

B-9032 GENT

TEL: (+) 32-9-257 08 80

FAX: (+) 32-9-257 08 85

www.pronorbelgium.com

E-mail: info@pronor.be