

OFFICE DIGITAL & ANALOGUE TELEPHONES



Operator console set model 24BTSXH

(Shown with push button extension console DSS110)

Specifications.

Power requirements: Drawn from the telephone line.
 Ringing tone volume: Adjustable on front.
 Dialling system : DTMF
 Speech channels : 2 and 1 data channel.
 Display : 8 lines
 Push buttons : 34 programmable and 14 fixed.
 Including handsfree operating.
 Extension console : 100 programmable push buttons
 and 10 fixed buttons.
 Temperature range : 0C° to +40C°
 Approvals : Approved in most countries by
 telecommunication government.
 Dimensions (LxWxD) : 230x180 (380)x70mm
 Shipping weight : 0,5Kg (1Kg)
 Value between () is including the DSS100 console



Executive set model 12BTX

Specifications.

Power requirements: Drawn from the telephone line.
 Ringing tone volume: Adjustable on front.
 Dialling system : DTMF
 Speech channels : 2 and 1 data channel.
 Display : 2 lines
 Push buttons : 10 programmable and 12 fixed.
 Including handsfree operating.
 Temperature range : 0C° to +40C°
 Approvals : Approved in most countries by
 telecommunication government.
 Installation : Desk top. For wall mounting
 order wall mounting bracket
 model DXE-2 BWMK
 Dimensions (LxWxD): 230x180x70mm
 Shipping weight : 0,5Kg



Standard set model DX2-DSL

Specifications.

Power requirements: Drawn from the telephone line.
 Ringing tone volume: Adjustable on front.
 Dialling system : DTMF
 Speech channels : 1 channel.
 Push buttons : - Transfer button.
 - Hold button.
 - Message waiting light.
 Including handsfree operating.
 Temperature range : 0C° to +40C°
 Approvals : Approved in most countries by
 telecommunication government.
 Installation : Desk top. For wall mounting
 order wall mounting bracket
 model DXE-2 WMK
 Dimensions (LxWxD): 220x170x60mm
 Shipping weight : 0,4Kg



Model Temporis 150

Analogue telephone with 8 one touch keys

Specifications

Construction : Carbon black PVC
 Mounting : Desk or wall mounted.
 Power requirements: analogue line from PABX
 Controls : handset receiver volume
 Ringer tone: 3 positions
 Ringer volume: 4 positions
 Switch DTMF/Pulse
 Indicators : visual ring indicator.
 Flash key : 630ms
 Microphone : electret
 Connection : RJ11
 Dial memory : 8 at max. 21 digits
 Temperature range : 0C° to +50C°. (20-80% humidity)
 Dimensions (LxWxH): 225 x 160 x 80mm.
 Shipping weight : 0,5Kg