

## EXPLOSION PROOF OUTDOOR TELEPHONE



**Model 351-001**

### FEATURES AND BENIFITS

- Wall mounted with integrated ringer.
- Sealed DTMF keypad in metal.
- CSA,NRTL/C and UL hazardous area approved for Class I, Division 2
- Robust and weather resistant. Carbon loaded glass –filled polyester handset.
- Hearing aid compatible handset and volume control in handset.
- Noise cancelling microphone.

### Options.

- LD = Keydoor lock  
SK = Spring door return.

Model 351-001 is an outdoor wall mounted explosion proof telephone suitable for use in a Division 2 area and for direct connection to any analogue PABX. The unit has been designed for continuously operation in chemical industry, refineries and all places where hazardous areas occur.

The telephone withstand acids, oils, an UV radiation.

### Specifications.

Power requirements	: 24...60VDC drawn from the telephone line. (20mA...60mA)
Field connection	: gland entry fixed cable 3 meter at the end RJ 11.
Mounting	: 4 screws
Ringing tone	: 95dbA.
Dialling system	: DTMF
Temperature range	: Minus 40C <sup>o</sup> to +60C <sup>o</sup>
Protection	: IP65
Approvals	: Class I, DIV.2 Groups A,B,C,D.    Class II, DIV.2 Groups G and Coal dust.
Dimensions (WxHxD)	: 239x334x188mm
Shipping weight	: 4Kg