

## ANALOGUE PROFESIONAL INDOOR INTERCOM STATIONS



**Model EE442**  
(Clean room intercom)

### Specifications.

Construction	: Grey moulded shock proof ABS with flat foil front.
	Desinfectable front cover.
Mounting	: Flush mounted.
Power requirements	: drawn from the central exchange.
Cabling	: Standard telephone cable 2x2x0,6mm2 (800mtr)
Microphone	: Electret type.
SPL (1Watt/1Mtr)	: 82dB at 50-Ohm speaker. 95 dB at full power.
Frequency range	: 200Hz - 9000Hz
Protection	: IP54
Keyboard	: Encapsulated REED contacts.
Temperature range	: Minus 40C <sup>o</sup> to +90C <sup>o</sup> . (95% humidity)
Dimensions (LxWxD)	: 264x132x63mm
Shipping weight	: 0,7Kg

### OPTIONS

UPD-1	= Flush mount installation box.
GA 442	= wall mount installation box



**Part UPD-1**  
(Flush mount box)

The model EE442 is an indoor flush mounted hands-free intercom station provided with a full selection keypad. The unit is ideal for applications where a clean area is required such as hospitals operation quarters and pharmaceutical or electronic production areas.

The communication is semi-duplex (speak/listen function controlled by voice). All stations are provided with a red optical indication soon the microphone of the station is activated.