

CAMERA CONTROL UNIT FOR TIN BATH.



Model CCP- 001 Tin bath camera control unit
(Right side panel. Left side panel will have same layout.)


FEATURES AND BENEFITS

- Maximum seven (7) cameras.
- Joy stick for control of EXIT camera.
- Built in "Temperature" alarm.
- Zoom, focus and iris control.

Flat cable 2 meter long included.



Example of Installation of water-cooled camera control panels and video monitors.



Model CAM-C-10 Control/power supply

Above camera control unit is ideal for controlling water-cooled camera's with a remote zoom lens for float glass survey into a Tin bath.
One panel model CCP-01 with control/power supply model CAM-C-10 will operate a maximum of 7 left side camera's . The second panel with his corresponding CAM-C-10 will drive an identical quantity on the right side.
The CCP-01 panel is connected with a flat cable of 2 meter long (25 pole connector) to their control/power supply unit model CAM-C-10.

Specifications.

Construction : Aluminium frontplate with burned in texts.
Mounting : CCP-001 control panel: Flush mounted. CAM-C-10: DIN rail mounted
Power requirements: drawn from the CAM-C-10 what requires 120VAC-230VAC/50-60Hz or 24VDC/5A
Cabling : Done by pre-fixed 2 meter long flat cables between panel and CAM-C-10.
Protection : IP23
Temperature range : 0C° to +40C°. (95% humidity)
Dimensions (HxWxD): Control panel 185x290x90mm Weight 1 Kg CAM-C-10 : 385x120x95 weight 3Kg
Cut out dimensions : H=159 W=272mm