

FIXED INDUSTRIAL OUTDOOR COLOUR CAMERA IP66



Model PR-FDC-001

(Shown with standard included surface mount box.)

FEATURES AND BENIFITS

- Vandal proof construction and IP 66 housing.
- Automatic "Day/Night" sensing providing excellent pictures and IR view during night.
- Suitable for wall, ceiling and pole mounting. Unique 3-D camera orientating system allows positioning of camera in all directions.
- Different power supplies and video standards available. (USA or Europe)

Options:

Add abbreviation behind the model number in order to obtain the requested option.

UTP = adapter for UTP twisted pair video output.

WMT= Wall mount bracket.

PMT = Pole mount bracket.


CMT = Corner mount box.



WMT



PMT



CMT

The model PR-FDC-001 is a colour fixed camera mounted into a vandal proof IP66 housing. The camera unit is provided with a manual variable lens between 3-9mm or 9-22mm. Specify when ordering.

Only a coaxial cable (or fiber, or twisted pair) and power supply cabling is required for proper operation.

The model PR-FDC-001 is ideal for general-purpose applications into an industrial area and is highly recommended for process survey or site access video control requiring high definition picture at low illumination.

Specifications

Power	: 12 to 28VDC or AC 50/60Hz	6Watt
Cable entry	: 1 each PG 16 top and side entry. When using mounting brackets, cables will pass through the bracket.	
Minimum scene illumination	: 0,35 Lux (50 IRE) day mode,	0,013 Lux (50 IRE) night sense+ mode (10 x Sensup)
CCD image sensor	: 1/3 " 752Hx582V .	
Resolution	:540TV lines	
Dimensions (ØxH)mm	:158 x 130,5 (including wall box)	
Lens	: variable focuslengt 3-9mm or 9-22mm.Wide = 95°x69°(HxV) Tele = 30°x23° (HxV) F=1	
Protection camera	: IP66	
Temperature range camera:	: Minus 50C° to +50C°	
Shipping weight	: 0,74 Kg	

PRONOR N.V.
Liefkensstraat 35A
B-9032 GENT

TEL: (+) 32-9-257 08 80

FAX: (+) 32-9-257 08 85

www.pronorbelgium.com

E-mail:info@pronor.be